



# **BLAST**



# PLAYFUL MID-SIZED POWERHOUSE

This isn't just a new Arctic Cat. It's a whole new category altogether. Combining a lighter, midsized frame with a best-in-class power-to-weight ratio, BLAST® offers easier handling and more responsive performance. And a 400 single-cylinder EFI 2-stroke engine means you're always packing plenty of muscle. With mountain, trail and sport utility models, this lighter weight heavy hitter is ready to go wherever you ride.

#### **KEY FEATURES**

#### **Blast LT**

- XTRA-ACTION™ rear suspension
- One-piece tunnel
- Standard electric-key start
- 146" Cobra track
- Standard rear rack
- Push-button reverse

#### Blast ZR

- SLIDE-RAIL rear suspension
- One-piece tunnel
- $\bullet \; \mathsf{Standard} \; \mathsf{electric}\text{-}\mathsf{key} \; \mathsf{start}$
- 121" standard track
- 4" low-height windshield
- Push-button reverse

#### Blast M

- ALPHA ONE® single-beam rear suspension
- One-piece tunnel
- Standard electric-key start
- 146" Challenger track
- 4" low-height windshield
- Push-button reverse

#### Blast M LTD 4000

- EFI single cylinder 400 engine
- ALPHA ONE® single-beam rear suspension
- FOX Float® 3 shocks
- 36" ski stance
- Liquid cooled
- Turn-key electric start
- Lightweight hood
- 146" Challenger track 2" lug

	BLAST LT 4000	BLAST ZR 4000	BLAST M 4000	BLAST M LTD 4000
ENGINE				
ENGINE	4000			
TYPE	2-stroke			
DISPLACEMENT (CC)	397cc			
COOLING	Liquid			
CYLINDERS	1			
FUEL CAPACITY (GAL.)	11.7			10.4
OIL SYSTEM CAPACITY (QUART)	3.25			
POWERTRAIN				
DRIVE CLUTCH	CVTech Trailbloc			
DRIVEN CLUTCH	CVTech Invance			
SUSPENSION				
FRONT SUSPENSION	Arctic Mountain Suspension™ (AMS)			
SKI SHOCKS		Hydraulic twin tube		FOX FLOAT 3
REAR SUSPENSION	XTRA-ACTION™ rear suspension w/ dual shocks and adjustable torsion springs  ALPHA ONE™ single-t			peam rear suspension
FRONT TRACK SHOCK	Hydraulic twin tube			Arctic Cat IFP 1.5
REAR TRACK SHOCK	Hydraulic twin tube			FOX FLOAT 3
DIMENSIONS				
CHASSIS OVERALL LENGTH (IN.)	128	115	12	8
CHASSIS OVERALL WIDTH (IN.)	44-45 44-46		44-46	42.5-44.5
CHASSIS OVERALL HEIGHT (IN.)	51	45	48	
TRACK TYPE	Cobra	Standard	Challenger	
TRACK WIDTH (IN.)	15	14	15	
TRACK LENGTH (IN.)	146	121	146	
LUG (IN.)	1.6	1	2	
SKI STANCE (IN.)	37.5-38.5	Adjustable	37-39 Adjustable	35.5-37.5 Adjustable
INSTRUMENTATION				
TYPE OF GAUGE	Digital			
FEATURES				
STARTER	Electric - key			
HEADLIGHTS	Halogen - one bulb			
WINDSHIELD	15.5" height		4" low	
COLOR	Black/Fire Red	Black/Medium Green	Black/Skye Blue	Phantom Gray/Spark Orange
STANDARD FEATURES	Hand and thumb warmer, rear rack, tether switch	Hand and thumb warmer, tether switch, mountain seat	Hand and thumb warmers, tether switch	Hand and thumb warmer, lightweight mountain seat, tether switch

#### WINTER ESSENTIALS KIT (BLAST LT)

- Pro Climb bumper
- Handlebar bag

### PRO KIT (BLAST M)

- Pro Climb bumper Handlebar bag
- Mountain pack

## TRAIL BLAZER KIT (BLAST ZR)

- Pro Climb bumper • Trail Pack
  - High touring windshield (15")



Black/Fire Red

• Hitch kit









WARNING: Arctic Cat snowmobiles can be hazardous to operate. Be sure to read and understand your owner's manual and please pay special attention to the safety instructions. All riders should wear a helmet, eye protection, and protective clothing. Riding and alcohol/drugs don't mix. Never attempt maneuvers beyond your capabilities. Arctic Cat recommends that all riders take a training course. For additional safety and training information, please see your dealer or call 1-800-887-2887. Vehicles shown may include options not included on base model. All materials, specifications, product offerings, accessories, and pricing are subject to change without notice. ADAPT, ALPHA ONE, AMS, ARCTIC CAT, ARCTIC MOUNTAIN SUSPENSION, ARS, ASCENDER, ATAC, AWS, BLAST, C-TEC2, C-TEC4, HARDCORE, NORSEMAN, POWER CLAW, PRO CLIMB, RIOT, SLIDE-ACTION, THUNDERCAT, XTRA-ACTION, and ZR are trademarks or registered trademarks of Arctic Cat Inc. All rights reserved. For more information, visit: www.arcticcat.com.

© 2022 Textron Specialized Vehicles Inc. 82667-63 (Rev. 01/2022)